GLOBAL INDO BUANA

Truck Mounted Crane 12 Ton

www.globalbuana.com



About **Our Vehicle**

About Truck Chasis

UD TRUCKS

The vehicle chassis that we use in this TMC unit is the UD Quester CWE 280 Truck. This truck has several advantages, including:

- Fuel efficient
- Has an environmentally friendly PTO feature
- Has a real-time fuel coach feature
- Has a cabin specifically designed for operations in mining areas
- Has a Full Air Brake braking system
- Has a 9-speed manual transmission
- Has a 6×4 wheel configuration
- Has a GH8E engine
- Has Euro 5 standard exhaust emissions

About Crane

SANY

The type of crane used is the Sany SPK36080, with the following advantages:

Lifting Moment	: 341.0 kNm (34.8 mt)
Max. Lifting Capacity	: 12.000 kg (12 ton)
Max. Hydraulic Outreach	: 12.1 m
Slewing Angle	: 400 (degree symbol)
Slewing Torque	: 37.3 kNm (3.8 mt)
Operating Pressure	: 33 Mpa (330 bar)
Pump Capacity	: 55-80 l/min

Our **Contact**

+62 21 2524 915

+62 812 9931 4637

marketing@globalbuana.com

www.globalbuana.com

Office

Jl Penjernihan 1 No 12 B, Bendungan Hilir, Tanah Abang, Jakarta Pusat Indonesia, 10210.

Detail **Information**

Truck Type	:	UD Truck Quester CWE 280 6X4R WB6100MM Euro 5
Engine Specifications	:	6 Cylinder, 7698 CC, 280 HP, 2.200 RPM.
Fuel Specification	:	Diesel Fuel (Max. 315L), with additional AdBlue (Max. 50L)
Dimension	:	2500 mm (W), 11875 mm (L), 3400 mm (H)
Empty Vehicle Weight Allowable Combination	:	15095 kg
Weight (JBB/JBKI) Total Allowable Vehicle	:	26000 kg
Combination Weight	:	24000 kg
Types of Vehicle bodies	:	Dropside Sixways (8300 x 2460 x 600) mm

Crane Type	:	Sany SPK36080 (Articulated Crane Model)
Lifting Moment	:	341.0 kNm (34.8 mt)
Max. Lifting Capacity	:	12.000 kg
Max. Hydraulic Outreach	:	12.1 m
Slewing Angle	:	400 (symbol derajat)
Slewing Torque	:	37.3 kNm (3.8 mt)
Operation Pressure	:	33 Mpa (330 bar)
Pump Capacity	:	55-80 l/min

Certified:

- **SIO Migas Certification for Operator**
- **SILO Migas Certification**
- **SILO Depnaker Certification**

